



		width	height	depth	seat width/height	arms height	unit weight kg.
6090		88	30	88			9.000
6091 fire tested version**		88	30	88			9.000
6092		88	58	88	63/30		21.000
6093 fire tested version**		88	58	88	88/30		21.000
6094		88	58	88	63/30	57	23.000
6095 fire tested version**		88	58	88	63/30	57	23.000
6096		88	58	88	63/30	57	23.000
6097 fire tested version**		88	58	88	63/30	57	23.000

**6090 / 6091 / 6092 / 6093
6094 / 6095 / 6096 / 6097**

02/orange	
03/white	
09/black	

Material
Seat and backrest: soft polyurethane with fabric upholstery
Feet: transparent polycarbonate

	level achieved
EN 1022:1998	Compliant
EN 1728:2000	
6.2.1	(maximum level) 5
6.2.2	(maximum level) 5
6.6	(maximum level) 5
6.7	(maximum level) 5
6.10	(maximum level) 5
6.15	(maximum level) 5
6.16	(maximum level) 5
6.17	(maximum level) 5

**IT UNI 9175, EN1021 fire reaction test
class 1 IM ministerial certification
M1848D20D1IM00008

UK Standard BS5852 S5, BS 7176
"Medium Hazard" - S.I. 1324

US CALIFORNIA Standard TB 117

packaging	quantity	weight kg.	volume m ³	size
6090	1	24.000	0.305	92X36X92
6091	1	24.000	0.305	92X36X92
6092	1	27.400	0.550	92X65X92
6093	1	27.400	0.538	92X65X92
6094	1	31.000	0.562	93X65X93
6095	1	31.000	0.562	93X65X93
6096	1	31.000	0.562	93X65X93
6097	1	31.000	0.562	93X65X93